

A limitless supply of heat A major boost to efficiency

Versatile cylinder technology for hot water and heating energy in one



It's simply ingenious – while we're still nice and comfortable in bed, our cylinder is keeping enough hot water at the ready. It's then just a matter of using it when we freshen up for the day ahead.

Comfort through technology



Giving the future a green light

Renewables help to determine where our energy will come from in the future. More and more people are recognising the benefits of green electricity for their homes. We too see electricity as the energy source of the future.

Turning the tide ourselves

Power companies, politicians and society have been seeking viable alternatives to fossil fuels for a long time. Fossil fuels are exhaustible resources that pollute the environment. So why not simply tap into the heat contained in the sun, air, water and ground, and put it to use in your home?

You are bound to have some concerns about the energy efficiency of your house. Perhaps you would like to change to a futureproof energy supply. The largest energy consumer is your heating system: almost 80 % of the energy you consume goes into heating and hot water. There is therefore great potential for an energy transition in your home.



Produce usable heat even more efficiently

If you rely on environmental or solar energy to heat your home and domestic hot water, installing a system cylinder makes perfect sense. After all, we don't always need heat at the time it's produced. These appliances store heat as hot water so that you can use it whenever you need to. We have the right cylinder for every type of building and set of circumstances.

Good reasons to enjoy your home comforts

- › Efficient and reliable heat pump operation thanks to specific system cylinders
- › Storage of solar heat with minimum losses
- › Effective use of more cost-efficient tariffs as well as your own solar power



Practical storage of renewables

Cylinders really are multi-talented. They not only keep a supply of heat ready for when you need it, but also improve the efficiency of your heating system or heat pump. To help you choose the right cylinder for your needs, it's important to understand the difference between the thermal cylinder solutions – buffer cylinders support your heating system, whereas DHW cylinders reliably supply your home with domestic hot water.

Choosing the right cylinder

Take the heat source into account

Most cylinders are designed to be used in combination with a heat pump. Other models are available, however, that can be used in conjunction with oil or gas heating. Plus, if you want to integrate a solar thermal system, we have a range of suitable SOL versions available.

Select the right size

The size of the cylinder has a significant impact on its efficiency. If you opt for a smaller model, the heat generator needs to operate at full load in short intervals, which uses a lot of energy. If the cylinder is oversized, you will have unnecessarily high standby energy losses.

Decide where to install

The ideal, all-round efficient solution is to install both a buffer cylinder and a DHW cylinder. If there isn't enough space in your home to accommodate the two appliances separately, STIEBEL ELTRON has the answer – our integral cylinders are compact units that house both types of cylinders in one casing.

Make the best choice for all your plans

DHW cylinders



Page 08

SBB 301-302 WP
SBB 401-501 WP SOL

Model	SBB 301-302 WP SBB 401-501 WP SOL
Detached and two-family house	■ ■
Apartment building	■
Commercial large scale system	
Heating cooling	
Domestic hot water	■
Nominal capacity	301, 290, 395, 495 l
Combination with heat pump	■
Combination with solar gas	■ ■
Product class	Premium



Page 10

SBB 300-500-1 Plus

Model	SBB 300-500-1 Plus
Detached and two-family house	■ ■
Apartment building	■
Commercial large scale system	
Heating cooling	
Domestic hot water	■
Nominal capacity	314, 418, 522 l
Combination with heat pump	■
Combination with solar gas	
Product class	Plus



Page 11

SBB 600-1000 WP SOL

Model	SBB 600-1000 WP SOL
Detached and two-family house	- ■
Apartment building	■
Commercial large scale system	■
Heating cooling	
Domestic hot water	■
Nominal capacity	565, 741, 836 l
Combination with heat pump	■
Combination with solar gas	■ ■
Product class	Plus

Integral cylinders



Page 16

HSBB 180 Plus
HSBC 180 Plus

Model	HSBB 180 Plus HSBC 180 Plus
Detached and two-family house	- ■
Apartment building	
Commercial large scale system	
Heating cooling	■ ■
Domestic hot water	■
Nominal capacity	178 l (buffer cylinder 80 l)
Combination with heat pump	■
Combination with solar gas	
Product class	Plus



Page 19

HSBB 200

Model	HSBB 200
Detached and two-family house	■ -
Apartment building	
Commercial large scale system	
Heating cooling	■ ■
Domestic hot water	■
Nominal capacity	181 l
Combination with heat pump	■
Combination with solar gas	
Product class	Plus

Buffer cylinders



Page 20

SBP 200-700 E
SBP 700 E SOL

Model	SBP 200-700 E SBP 700 E SOL
Detached and two-family house	■ ■
Apartment building	
Commercial large scale system	
Heating cooling	■ ■
Domestic hot water	■
Nominal capacity	207, 415, 703, 720 l
Combination with heat pump	■
Combination with solar gas	■ ■
Product class	Plus

Integral cylinders



Page 12

SB-VTI 100-500

■ | ■

113, 147, 192, 295, 412, 496 l

Trend



Page 13

HSBC 300 cool
HSBC 300 L cool

■ | -

■ | ■

270 l (buffer cylinder 100 l)

Premium



Page 14

HSBC 200
HSBC 200 L

■ | -

■ | ■

168, 180 l (buffer cylinder 100 l)

Premium | Plus

Inst. water cylinders



Page 22

SBP 1000/1500 E (cool)
SBP 1000/1500 E SOL
SBP 1010 E (cool)

- | ■

■ | ■

■ | ■

979, 1006, 1473, 1503 l

Plus



Page 24

SBP 100

■ | -

■

■ | -

100 l

Plus



Page 24

SBP 100 classic

■ | -

■

■ | ■

100 l

Trend



Page 25

SBS 601-1501 W
SBS 601-1501 W SOL

■ | ■

■

■ | -

599, 613, 740, 759, 916, 941, 1430, 1500 l

Premium



Choose an efficient partner for your heat pump

SBB WP (SOL) DHW cylinder

If you value high DHW convenience and a good level of efficiency, these cylinder solutions are for you. These appliances work together with a heat pump to supply hot water in detached or two-family houses.

Making effective use of the sun

And that's not all these appliances can do. One of our cylinder models is equipped with a special smooth tube indirect coil. This allows you to make full and efficient use of the heat yield from your solar thermal system.

Top product features

- › For DHW heating in a detached or two-family house
- › Designed for different heat pumps
- › Special version can be combined with a solar thermal system



DHW heating

Make the link between hot water and high efficiency

SBB Plus DHW cylinder



Our solutions allow you to make good use of water heated with environmental energy. You simply need to combine your eco-friendly heating heat pump with this DHW cylinder. It's also an effective way to boost energy efficiency. Under ErP rules, the appliance is rated class B.

Versatile, long term use

Remarkable efficiency is just one of the many benefits that you can look forward to. Thanks to integral corrosion protection, you can continue to enjoy your cylinder for many years to come. It doesn't matter whether you live in a detached or two-family house, the appliance is suitable for use in both types of building.

Top product features

- › DHW cylinder for combination with heating heat pumps
- › Low standby losses for efficient operation
- › Integral corrosion protection
- › Choice of 300, 400 or 500 litre version, depending on DHW demand



DHW heating

Store hot water on a grand scale

SBB WP SOL DHW cylinder



Looking for a hot water supply on a grand scale? No problem! These cylinders are suitable for combination with large heat pumps such as those used in detached or two-family houses and commercial buildings. If you find that your demand increases, you can easily retrofit a booster heater.

Soak up all the sun

These DHW cylinders also use solar heat on a large scale. With a nominal capacity of more than 800 litres, they allow you to store the heat obtained even from larger solar thermal systems with ease. Where demand is greater still, simply link the cylinders in series.

Top product features

- › Large nominal cylinder capacity of more than 800 litres
- › Even better efficiency thanks to highly effective thermal insulation
- › Increased service life due to corrosion protection as standard
- › Can optionally be equipped with a booster heater



DHW heating

Enjoy hot water at any time

SB-VTI DHW cylinder



This cylinder ensures that domestic hot water is available day and night – irrespective of whether it supplies just your home, or also your neighbour's. With a volume of up to 150 litres, it's an excellent choice for your detached house, but is also equally suitable for two-family houses.

The perfect combination

Easily combine the DHW cylinder with a heating heat pump to enjoy maximum convenience. The appliance can also be linked to an oil or gas heat generator if required. For ease of operation, we have also equipped it with a temperature controller and a thermometer.

Top product features

- › DHW cylinder for combination with heating heat pumps or other heat generators
- › Slimline format for easy integration into the space available
- › Integral corrosion protection



DHW heating

Save a good deal of space

HSBC 300 (L) cool integral cylinder



When it comes to accommodating multiple functions in a space saving design, this integral cylinder is far ahead of the pack. There's no need to install two cylinders next to one another – instead, you can use a single unit that has the DHW cylinder and the buffer cylinder arranged one on top of the other. As a result, you only need half as much installation space.

Control your system with ease

We have carefully matched both versions of this integral cylinder so that they can be used in a detached house in conjunction with one of our heat pumps. Plus, with the heat pump manager (WPM) built in, controlling your appliances couldn't be easier.

Top product features

- › Combi unit comprising a DHW cylinder and a buffer cylinder
- › For greater DHW convenience
- › Halves the installation space required for separate cylinders
- › Compact, reliable and energy saving
- › Perfect for combination with a heat pump
- › Can be integrated into a heating or cooling system
- › Connection of two heating circuits possible
- › With integral heat pump manager for even faster installation of the overall system (not with every version)



DHW heating



Heating



Cooling

Put together the perfect duo for your home

HSBC 200 (L) integral cylinder

Choose one appliance and get two cylinders. That's possible with this cylinder solution. This space saving combination of DHW cylinder and buffer cylinder gives you a capacity of up to 180 litres for a reliable supply to your home.

Never do without heat

Thanks to its carefully coordinated design, you can easily connect the integral cylinder to a suitable model from our range of efficient air source heat pumps. This ensures an absolutely reliable supply of domestic hot water and heating energy in your home.

Top product features

- › Combi unit comprising a DHW cylinder of up to 180 litres with a buffer cylinder
- › Halves the installation space required for separate cylinders
- › Compact, reliable and energy saving for use in detached houses
- › Perfect for combination with an air source heat pump for DHW heating and room heating
- › Connection of two heating circuits possible



DHW heating



Heating



Cooling





Form alliances for added convenience

HSBB 180 Plus DHW cylinder

Are you looking for a cylinder solution for your newly built detached house? Then you've come to the right place. Combine this indoor DHW cylinder with one of our outdoor heat pumps and enjoy high levels of convenience and cost savings – especially if your home is equipped throughout with underfloor heating. The cylinder integrates all hydraulic components for maximum practicality.

Top product features

- › Appliance installed indoors, incorporating all important hydraulic components
- › Compact, reliable and energy saving for use in detached houses
- › Perfect for combination with a heat pump installed outdoors
- › Can also be used for cooling via underfloor heating system or fan convectors

Skilful adaptation

When summer comes and it's time to turn the heating off, the cylinder also supports cooling via the heat pump and underfloor heating system. The minimalist design of the cylinder also helps it to look great in whatever installation room you choose.



DHW heating



Heating



Cooling

Benefit from a range of functions in the smallest of spaces

HSBC 180 Plus integral cylinder



This integral cylinder makes it easy for you to enjoy heating and hot water at any time, yet in a particularly economical way. The integral buffer cylinder stores thermal energy that isn't currently needed and releases it to the heating circuit when it is. At the same time, it also boosts the reliability of the system as a whole, to make sure that you're plentifully supplied.

Find your cool in the summer

An additional benefit of this integral cylinder is the option for cooling via an underfloor heating system or fan convectors. Despite this extensive functionality, you need nothing more than a compact appliance which takes up only minimal space, conveniently combined with an outdoor air source heat pump.

Top product features

- › Combi unit comprising a DHW cylinder and a buffer cylinder
- › Halves the installation space required for separate cylinders
- › Compact, reliable and energy saving
- › Perfect for combination with outdoor heat pumps for DHW heating and room heating
- › Can also be used for cooling



DHW heating



Heating



Cooling

Guarantee maximum storage convenience

HSBB 200 integral cylinder



This integral cylinder opens up a wide range of combination options. Thanks to built-in hydraulic components, you can link the cylinder and hydraulic module with a variety of different heat pump models.

Convenient control of the appliance's functions

This model has a small footprint – partly on account of its high level of integration and partly thanks to the built-in DHW cylinder. The appliance can be conveniently controlled using the integral heat pump manager (WPM). When it comes to the individual components, our precise workmanship comes to the fore – everything is well coordinated so that you can look forward to reliable, long term operation as well as maximum system efficiency.

Top product features

- › High level of integration for a space-efficient concept
- › Perfect for combination with our heat pumps, such as in matched sets with air source heat pumps
- › High DHW convenience thanks to a 200 litre enamelled DHW cylinder with internal indirect coil



Heating



DHW heating



Cooling

The perfect complement to your heat pump

SBP E (S0L) buffer cylinder

You've decided on an environmentally responsible heat pump and are now looking for an accompanying buffer cylinder. This model for detached and two-family houses is the perfect choice. If necessary, you can also connect an electric heater to the cylinder for a plentiful heat supply. If your heat pump supports reverse operation, the appliance can also store the water required for cooling.

Make use of thermal energy

Our range also includes a model equipped with a special indirect coil, which allows you to make efficient and effective use of the heat yielded by your solar thermal system.

Top product features

- › Designed for different heat pumps
- › Cooling operation possible
- › Individual cylinder selection subject to system size
- › Highly effective thermal insulation



Heating



Cooling





Overcome major challenges with ease

SBP E (cool | SOL) buffer cylinder

Well equipped for major challenges – the larger versions of this buffer cylinder can be easily linked to large, high performance heat pumps, including cascades. This solution is also ideal if you're planning to integrate a solar thermal system or additional heat generator to charge the buffer cylinder.

Enjoy the full range of functions

The larger versions of this cylinder are the preferred option for apartment buildings. A reliable operating pressure of 10 bar helps to ensure a particularly high level of reliability. If you opt to use the appliance for cooling as well, you'll have everything you need to enjoy the full range of functions offered by our heat pumps.

Top product features

- › Specifically sized for high heat pump outputs, e.g. cascades
- › Solar integration possible (special versions)
- › Cooling operation possible (special versions)
- › Thermal insulation as an optional accessory



Heating



Cooling

Gain space with efficient cylinder technology

SBP (classic) buffer cylinder



Two models, two masterpieces – each version of this buffer cylinder offers you its own particular benefits. The first model is the most compact buffer cylinder in our range and is designed for wall mounting. Once installed, it is particularly space saving and therefore makes an excellent choice if you have an energy efficient detached house with a low heat demand.

A practical, versatile solution

The second version has virtually no limitations on where it can be installed, as the heat pump and heating circuit connections can be made on the left or right. As a further practical benefit, you can also use this buffer cylinder for cooling.

Top product features

- › Ideal addition to small heat pump systems in detached houses
- › Wall mounting for a small footprint (special versions)



Heating

Let a strong team take care of the work

SBS W (SOL) instantaneous water cylinder



Smart technology in the smallest of spaces: you don't have to give up much room to accommodate this buffer cylinder and DHW cylinder combination. An additional benefit is the high level of hygiene – as the appliance contains a very effective indirect coil, it stores only small quantities of domestic hot water. The buffer cylinder retains heat for room heating whenever you need it.

Integrate solar energy

With one of our efficient heat pumps, you can easily connect an additional heat source. We also offer a version of the instantaneous water cylinder that allows you to enjoy the benefits of a solar thermal system as well.

Top product features

- › Space and price advantage due to two functions in a single cylinder
- › Wide range of applications through combination with solar thermal (special versions) or additional heat generators
- › Only one cylinder for DHW heating and room heating
- › Halves the installation space required for separate cylinders
- › Universal application options



DHW heating



Heating

Cylinders product comparison

Model		SBB 301 WP	SBB 302 WP	SBB 401 WP SOL	SBB 501 WP SOL
Product number		221360	221361	221362	227534
Rated capacity	l	301	290	395	495
Energy efficiency class		C	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	2.1	2.1	2.4	2.4
Surface, indirect coil	m ²	3.2	4.8	4	
Surface, indirect coil, top	m ²	3.2	4.8	4	5
Surface area, lower indirect coil	m ²			1.4	1.4
Max. permissible pressure	MPa	1	1	1	1
Max. recommended collector aperture area	m ²			8	10
Height/Diameter incl. thermal insulation	mm	1710/700	1710/700	1880/750	1988/810
Weight (dry)	kg	142	184	189	222
Product class Premium/Plus/Trend		■/-/-	■/-/-	■/-/-	■/-/-

Model		SBB 300-1 Plus	SBB 400-1 Plus	SBB 500-1 Plus
Product number		202487	202488	202489
Rated capacity	l	314	418	522
Energy efficiency class		B	B	B
Standby energy consumption/24 h at 65 °C	kWh	1.7	1.8	1.9
Surface, indirect coil, top	m ²	2	2.6	3.2
Max. permissible pressure	MPa	1	1	1
Height	mm	1619	1799	1904
Diameter incl. thermal insulation	mm	650	730	780
Weight (dry)	kg	111	139	182
Product class Premium/Plus/Trend		-/■/-	-/■/-	-/■/-

Model		SBB 600 WP SOL	SBB 800 WP SOL	SBB 1000 WP SOL
Product number		235906	235907	235908
Rated capacity	l	575	770	835
Standby energy consumption/24 h at 65 °C	kWh	2.7	3	3.4
Surface, indirect coil, top	m ²	5.7	6.2	6.2
Surface area, lower indirect coil	m ²	2	2.6	3.6
Max. permissible pressure	MPa	1	1	1
Max. recommended collector aperture area	m ²	12	14	17
Height	mm	1775	1943	2153
Diameter incl. thermal insulation	mm	970	1010	1010
Weight (dry)	kg	244	296	322
Product class Premium/Plus/Trend		-/■/-	-/■/-	-/■/-

Model		WDH 600 SBB	WDH 800 SBB	WDH 1000 SBB
Product number		235909	235910	235911
Standby energy consumption/24 h at 65 °C	kWh	2.7	3	3.4
Insulation for		SBB 600 WP SOL	SBB 800 WP SOL	SBB 1000 WP SOL
Height	mm	1803	2065	2275

Cylinders product comparison

Model		SB-VTI 100	SB-VTI 150	SB-VTI 200	SB-VTI 300	SB-VTI 400	SB-VTI 500
Product number		200156	200157	200158	200159	200160	200161
Rated capacity	l	113	147	192	295	412	496
Energy efficiency class		B		C	C	C	C
Standby energy consumption/24 h at 65 °C	kWh	1.1	1.4	1.5	2.2	2.5	2.7
Surface, indirect coil, top	m ²	1	1.1	1.3	1.5	1.9	2.3
Max. permissible pressure	MPa	0.6	0.6	0.6	0.6	0.6	0.6
Height	mm	1022	1262	1574	1552	1543	1813
Diameter incl. thermal insulation	mm	550	550	550	650	750	750
Weight (dry)	kg	66	81	96	126	188	213
Product class Premium/Plus/Trend		-/-/■	-/-/■	-/-/■	-/-/■	-/-/■	-/-/■

Model		HSBC 300 cool	HSBC 300 L cool
Product number		236686	238826
Rated capacity	l	100	100
Nominal capacity, DHW cylinder	l	270	270
Energy efficiency class		B	B
Standby energy consumption/24 h at 65 °C	kWh	1,5	1,5
Surface, indirect coil	m ²	3,3	3,3
Max. permissible pressure, buffer cylinder	MPa	0,3	0,3
Product class Premium/Plus/Trend		■/-/-	■/-/-

Model		HSBC 200	HSBC 200 L
Product number		233510	236684
Rated capacity	l	100	100
Nominal capacity, DHW cylinder	l	168	180
Energy efficiency class		B	B
Standby energy consumption/24 h at 65 °C	kWh	1,3	1,3
Surface, indirect coil	m ²	3,3	1,6
Max. permissible pressure, buffer cylinder	MPa	0,3	0,3
Height	mm	1908	1908
Weight (dry)	kg	203	185
Product class Premium/Plus/Trend		■/-/-	-/■/-

Cylinders product comparison

Model	HSBB 180 Plus		HSBC 180 Plus	
Product number	202926		202927	
Nominal capacity, buffer cylinder	l			80
Nominal capacity, DHW cylinder	l	178		178
Energy efficiency class		B		B
Standby energy consumption/24 h at 65 °C	kWh	1.29		1.29
Surface, indirect coil	m ²	1.59		1.59
Max. permissible pressure, buffer cylinder	MPa			0,3
Height/Width/Depth	mm	1280/694/917		1892/605/917
Weight (dry)	kg	100		145
Product class Premium/Plus/Trend		-/■/-		-/■/-

Model	HSBB 200	
Product number	235195	
Rated capacity	l	181
Nominal capacity, DHW cylinder	l	181
Energy efficiency class		B
Standby energy consumption/24 h at 65 °C	kWh	1.3
Surface, indirect coil	m ²	1.6
Height	mm	1328
Weight (dry)	kg	150
Product class Premium/Plus/Trend		-/■/-

Model	SBP 200 E		SBP 400 E		SBP 700 E		SBP 700 E SOL	
Product number	185458		220824		185459		185460	
Rated capacity	l	207	415		720		703	
Energy efficiency class		B	B					
Standby energy consumption/24 h at 65 °C	kWh	1.1	1.6		2.2		2.2	
Surface, indirect coil	m ²						2	
Surface area, lower indirect coil	m ²						2	
Max. permissible pressure	MPa	0.3	0.3		0.3		0.3	
Max. recommended collector aperture area	m ²						14	
Height	mm	1535	1710		1890		1890	
Diameter incl. thermal insulation	mm	630	750		910		910	
Weight (dry)	kg	58	81		185		216	
Product class Premium/Plus/Trend		-/■/-	-/■/-		-/■/-		-/■/-	

Model	SBP 1000 E		SBP 1500 E		SBP 1000 E SOL		SBP 1500 E SOL		SBP 1010 E		SBP 1010 E cool	
Product number	227564		227565		227566		227567		227588		227589	
Rated capacity	l	1006	1503	979	1473	1006	1503	1006	1006	1006	1006	1006
Standby energy consumption/24 h at 65 °C	kWh	3.6	4.1	3.6	4.1	3.5	4	3.6	3.5			
Surface, indirect coil	m ²			3	3.6							
Surface area, lower indirect coil	m ²			3	3.6							
Max. permissible pressure	MPa	0.3	0.3	0.3	0.3	0.3	0.3	1	1			
Max. recommended collector aperture area	m ²			20	30							
Height	mm	2300	2220	2300	2220	2300	2220	2300	2300			
Diameter incl. thermal insulation	mm	1010	1220	1010	1220	1010	1220	1010	1010			
Weight (dry)	kg	172	229	219	285	181	239	233	242			
Product class Premium/Plus/Trend		-/■/-	-/■/-	-/■/-	-/■/-	-/■/-	-/■/-	-/■/-	-/■/-			

Model	WDH 1000 SBP		WDH 1010 SBP		WDH 1500 SBP		WDH 1000 cool		WDH 1500 cool	
Product number	231929		201662		231930		231921		231922	
Standby energy consumption/24 h at 65 °C	kWh	3.6	3.6	4.1	3.5	4				
Insulation for		SBP 1000 E und E SOL	SBP 1010 E	SBP 1500 E und E SOL	SBP 1000 und 1010 E cool	SBP 1500 E cool				
Height	mm	2340	2340	2255	2340	2255				

Cylinders product comparison

Model		SBP 100	SBP 100 classic
Product number		185443	235200
Rated capacity	l	100	100
Energy efficiency class		C	C
Standby energy consumption/24 h at 65 °C	kWh	1.4	1.2
Max. permissible pressure	MPa	0.3	0.3
Height	mm	955	877
Diameter incl. thermal insulation	mm		510
Weight (dry)	kg	42,5	21
Product class Premium/Plus/Trend		-/■/-	-/■/-

Model		SBS 601 W	SBS 601 W SOL	SBS 801 W	SBS 801 W SOL	SBS 1001 W	SBS 1001 W SOL	SBS 1501 W	SBS 1501 W SOL
Product number		229980	229984	229981	229985	229982	229986	229983	229987
Rated capacity	l	613	599	759	740	941	916	1430	1399
Standby energy consumption/24 h at 65 °C	kWh	2.6	2.6	2.9	2.9	3.5	3.5	3.6	4.1
Max. permissible pressure, DHW	MPa	1	1	1	1	1	1	1	1
Surface area, lower indirect coil	m ²		1.5		2.4		3.2		3.7
Max. permissible pressure	MPa	0.3	0.3	0.3	0.3	0.3	0.3	0.3	0.3
Max. recommended collector aperture area	m ²		12		16		20		30
Height	mm	1665	1665	1830	1830	2240	2240	2155	2155
Diameter incl. thermal insulation	mm	970	970	1010	1010	1010	1010	1220	1220
Weight (dry)	kg	135	180	150	195	175	220	236	291
Product class Premium/Plus/Trend		■/-/-	■/-/-	■/-/-	■/-/-	■/-/-	■/-/-	■/-/-	■/-/-

Model		WDH 601 SBS	WDH 801 SBS	WDH 1001 SBS	WDH 1501 SBS
Product number		231925	231926	231927	231928
Standby energy consumption/24 h at 65 °C	kWh	2.6	2.9	3.5	4.1
Insulation for		SBS 601 W, W SOL	SBS 801 W, W SOL	SBS 1001 W, W SOL	SBS 1501 W, W SOL
Height	mm	1775	1940	2350	2265

Recharge your energy with ours

We need energy to live. As a family business, we endeavour to ensure that energy will still be available in tomorrow's world. That is why we advocate environmentally responsible and efficient building services that safeguard investment. We act for the future – yours and ours.

Since 1924, STIEBEL ELTRON has been synonymous with reliable solutions for domestic hot water, heating, ventilation and cooling. We maintain a clear focus in the energy debate: electricity, preferably harnessed from renewables, is the energy of the future. That is why we rely on approximately 3900 employees around the world for efficient heating solutions with green technologies.

From the design and manufacture of your appliance through to its maintenance, we systematically apply our expertise, strength of innovation and experience – gained from working with customers with high standards, such as yourself, and from the sale of more than two million appliances each year. We have the right solution to meet any requirement. Solutions designed to raise the level of convenience in your home today and still be up to date tomorrow.

You can see first hand our commitment to green technology by visiting the Energy Campus at our head office in Holzminden, Germany. This training and communication centre is our flagship project for sustainable and resource-efficient construction. It combines the highest standards of architectural and communication quality. As a PlusEnergy building, it generates more energy than it consumes. Come and experience what our name stands for – in theory and practice.



Your local trade partner:



For new and interesting information on our products, visit
www.stiebel-eltron.com or consult your local trade partner.

STIEBEL ELTRON International GmbH | Dr.-Stiebel-Straße 33 | 37603 Holzminden | Germany
info@stiebel-eltron.com | www.stiebel-eltron.com
Managing Director Dr. Nicholas Matten | VAT ID number DE811150571 | HRB 119307

Legal notice | In spite of our careful efforts, we are not liable for any inaccuracies in the content of this brochure. Information concerning equipment levels and specifications is subject to modification. The equipment features described in this brochure are non-binding regarding the specification of the final product. Due to our policy of ongoing improvement, some features may be changed or even removed. Please consult your local dealer for information about the very latest equipment features. The images in this brochure are for reference only. The illustrations also contain installation components, accessories and special equipment that do not form part of the standard delivery. Reprinting of all or part of this brochure is only lawful with the publisher's express permission.