

# DHE 18/21/24

PRODUCT-NO.: 202656

## Use water your way

Every one of our fully electronic instantaneous water heater models provides hot water at the exact temperature you have set at all times. No ifs or buts. The 4i technology ensures that nothing interferes with the outlet temperature. Enjoy constant hot water in the shower, even if somebody needs to wash their hands at the washbasin beside you.



## Make all your own choices

The haptic rotary selector ensures the appliance is very easy to operate: intuitive, instant, precise.

## Reliably glean key information at a glance

The illuminated multifunction display gives you a clear overview of your required water temperature, the ECO level and current power consumption. You can check energy consumption, flow rate, time, status and service information in the lower part of the display.

## The main features

Instantaneous water heater with full electronic control

---

Accurate water temperature delivery at all times thanks to 4i technology

---

Sufficient hot water for multiple draw-off points

---

Easy to use backlit multifunction display

---

Energy and water consumption LEDs

---

Particularly economical operation with ECO mode

---

Individual memory buttons for setting preferred temperatures

---

Additional functions such as a temperature limit, wellness shower program, automated bath filling and childproofing for greater convenience and safety



Type	DHE 18/21/24	DHE 27
Part no.	202656	202657

## Technical data

Rated voltage	400 V	400 V
Rated voltage 1	380 V	380 V
Rated voltage 2	400 V	400 V
Rated voltage 3	415 V	
Rated output	18/21/24 kW	27 kW
Rated output 1	16.2/19/21.7 kW	24.4 kW
Rated output 2	18/21/24 kW	27 kW
Rated output 3	19.4/22.6/25.8 kW	
Rated current	29/31/35 A	39 A
Rated current 1	27.6/29.5/33.3 A	37.1 A
Rated current 2	29/31/35 A	39 A
Rated current 3	30.1/32.2/36.3 A	
Fuse protection	32/32/35 A	40 A
Fuse protection 1	32/32/35 A	40 A
Fuse protection 2	32/32/35 A	40 A
Fuse protection 3	32/32/40 A	
Frequency	50/60 Hz	50/- Hz
Frequency 1	50/60 Hz	50/- Hz
Frequency 2	50/60 Hz	50/- Hz
Frequency 3	50/- Hz	
Phases	3/PE	3/PE
Resistivity $\rho_{15} \geq$	900 $\Omega$ cm	900 $\Omega$ cm

<b>Conductivity <math>\sigma_{15 \leq}</math></b>	1111 $\mu\text{S}/\text{cm}$	1111 $\mu\text{S}/\text{cm}$
<b>IP rating</b>	IP 25	IP 25
<b>Temperature setting</b>	20–60 °C	20–60 °C
<b>Colour</b>	white	white
<b>ON</b>	>2.5 l/min	>2.5 l/min
<b>Height</b>	466 mm	466 mm
<b>Width</b>	225 mm	225 mm
<b>Depth</b>	116 mm	116 mm
<b>Weight</b>	3.10 kg	3.10 kg

## **Contact information**

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **[info@stiebel-eltron.co.za](mailto:info@stiebel-eltron.co.za)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.