

# UP 25/7.5 PCV

ACCESSORIES

PRODUCT-NO.: 201620

## The main features

Electronically controlled circulation pump with variable differential control

---

Energy efficiency index (EEI): 0.20

---

Can be controlled via either a PWM signal or differential pressure

---

Delivery head max. 10 m

**UP 25/1-8 PCV**

Product-No.: 205285

**UP 30/1-8 PCV**

Product-No.: 205286



Type	UP 25/1-8 PCV	UP 25/7.5 PCV	UP 30/1-8 PCV
Part no.	205285	201620	205286

## Technical data

Energy Efficiency Index EEI	0.20	0.20	0.20
Connection	G 1 1/2	G 1 1/2	G 2
Delivery head	8.00 m	8.40 m	8.00 m
Max. flow rate	9.50 m³/h	4.00 m³/h	9.00 m³/h
Power consumption	200 W	10-60 W	130 W
Rated voltage	230 V	230 V	230 V
Control via 0-10 V signal with IF module	x	-	x
Control via differential pressure	x	x	x
Control via PWM signal	x	x	x
Installation length (centre distance)	180 mm	180 mm	180 mm

**Contact information**

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **[info@stiebel-eltron.co.za](mailto:info@stiebel-eltron.co.za)**

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.