WPKI-HK DN 25

ACCESSORIES

PRODUCT-NO.: 206627



The main features

Pump assembly for heating circuit without mixer

For combination with buffer cylinders

WPKI-HK DN 32
Product-No.: 209054

WPKI-HK DN 40
Product-No.: 209055

Type	WPKI-HK DN 25	WPKI-HK DN 32	WPKI-HK DN 40
Part no.	206627	209054	209055

Technical data

Connection, above	G 1	G 1 1/4 I	G 1 1/2 I
Connection, below	G 1 1/2 A	G 2 A	DN 40 PN6
Circulation pump type	Wilo Para SC 25/6-43	Grundfos UPML 32-105 AUTO	Wilo Yonos MAXO plus 40/0.5-12
Height	383 mm	441 mm	816 mm
Width	250 mm	250 mm	320 mm
Depth	213 mm	218 mm	554 mm
Energy Efficiency Index EEI	0.20	0.23	0.20
Delivery head	6.70 m	10.00 m	12.00 m
Max. flow rate	7.80 m³/h	13.60 m³/h	28.30 m³/h

Contact information

You have questions? We appreciate to help you:
Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.