

WPKI-HKM 24 DN 32

ACCESSORIES PRODUCT-NO.: 206628

The main features

Including thermal insulation and wall mounting bracket

Complete with built-in high efficiency pump and 24 V mixer motor

Pump assembly for heating circuit with mixer





WPKI-HKM 24 DN 40 Product-No.: 206632







Туре	WPKI-HKM 24 DN 32	WPKI-HKM 24 DN 40
Part no.	206628	206632

Technical data

Connection, above	G 1 1/4 l	1 1/2 l
Connection, below	G 2 A	DN 40 PN6
Circulation pump type	Grundfos UPML 32-105 AUTO	Wilo Yonos MAXO plus 40/0.5-12
Height	441 mm	811 mm
Width	250 mm	320 mm
Depth	293 mm	554 mm
Energy Efficiency Index EEI	0.20	0.20
Delivery head	10.00 m	12.00 m
Max. flow rate	11.40 m³/h	17.70 m³/h



Contact information

You have questions? We appreciate to help you:
Call +27 10 001 85 47 Write an email to info@stiebel-eltron.co.za

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.