

WPL-A 07.2 W Plus HK 230

AIR SOURCE HEAT PUMPS

PRODUCT-NO.: 208427

Added efficiency and welcome peace and quiet

With outstanding efficiency and exceptionally quiet operation, this air source heat pump installed outdoors for heating, cooling and hot water is bound to impress. It achieves an energy efficiency class of A+++ in new build or modernisation. Your existing building can also be heated extremely efficiently, regardless of its modernisation status. And this is equally possible via classic radiators or underfloor heating. Even at the lowest outside temperatures, you can enjoy cosy warmth and unbeatable hot water convenience at all times. In summer, you also have the option of cooling your home via underfloor heating.

Simply flexible through and through

On your flat roof, outside on the house wall or simply on the ground – with the right accessories and thanks to its exceptionally quiet operation, you have all the options for installing your heat pump. And it can be controlled just as flexibly. A few degrees warmer or pleasantly cool – it's up to you. Because you can control your preferred temperature easily and conveniently with the right accessories via an app. A visual plus too: for an even more aesthetic appearance, the plinth, wall mounting bracket and even the feet can be clad in the appropriate design.

Convenience and cost savings for you

Thanks to natural refrigerant R290 and this specially designed heat pump, you can heat even more efficiently and in a more eco-friendly way to deliver benefits that pay off. Do you own a photovoltaic system or are you planning on installing one? It can also be seamlessly integrated to utilise self-generated electricity for even greater cost savings.

The main features

Impressively efficient air source heat pump installed outdoors for heating and cooling

Exceptionally quiet operation for flexible installation options even with restricted space



WPL-A 10.2 W Plus HK 230

Product-No.: 208428



WPL-A 10.2 W Plus HK 400

Product-No.: 208429



WPL-A 13.2 W Plus HK 400

Product-No.: 208430

Easy to integrate visually thanks to a choice of colours in anthracite or white


Universal use with classic radiators or underfloor heating possible

Ideally suited for new build, modernisation or existing buildings

Futureproof thanks to the use of the natural refrigerant R290

Convenient operation via app, even when out and about (additional components required)

Low operating costs thanks to energy efficiency class up to A+++



Type	WPL-A 07.2 W Plus HK 230	WPL-A 10.2 W Plus HK 230	WPL-A 10.2 W Plus HK 400
Part no.	208427	208428	208429

Technical data

Energy efficiency class, heat pump W35 (A+++ → D)	A+++	A+++	A+++
Energy efficiency class, heat pump W55 (A+++ → D)	A+++	A+++	A+++
SCOP 35 °C (EN 14825)	5.09	4.96	4.96
SCOP 55 °C (EN 14825)	4.02	3.99	3.99
Heating output at A7/W35 (EN 14511)	3.05 kW	4.32 kW	4.32 kW
Heating output at A2/W35 (EN 14511)	3.29 kW	4.09 kW	4.09 kW
Heating output at A-7/W35 (EN 14511)	7.09 kW	10.07 kW	10.07 kW
Max. cooling capacity at A35/W7	6.51 kW	9.33 kW	9.33 kW
Cooling capacity at A35/W18, partial load (EN 14511)	3.15 kW	4.29 kW	4.29 kW
Max. cooling capacity at A35/W18	6.98 kW	10.51 kW	10.51 kW
COP at A7/W35 (EN 14511)	5.50	5.40	5.40
COP at A2/W35 (EN 14511)	4.57	4.54	4.54
COP at A-7/W35 (EN 14511)	3.25	3.15	3.15
Energy efficiency ratio at A35/W7 max.	2.97	2.76	2.76
Energy efficiency ratio at A35/W18, partial load (EN 14511)	5.29	5.46	5.46
Energy efficiency ratio at A35/W18 max.	4.28	4.01	4.01
Sound power level (EN 12102)	43 dB(A)	46 dB(A)	46 dB(A)
Min./max. application limits for heat source	-25 / 40 °C	-25 / 40 °C	-25 / 40 °C
Max. application limit on the heating side	75 °C	75 °C	75 °C
Height	960 mm	1144 mm	1144 mm

Width	1170 mm	1170 mm	1170 mm
Depth	727 mm	727 mm	727 mm
Weight	145 kg	166 kg	166 kg
Rated voltage, compressor	230 V	230 V	400 V
Refrigerant	R290	R290	R290
Colour	Signal white RAL 9003	Signal white RAL 9003	Signal white RAL 9003



Type	WPL-A 13.2 W Plus HK 400
Part no.	208430

Technical data

Energy efficiency class, heat pump W35 (A+++ → D)	A+++
Energy efficiency class, heat pump W55 (A+++ → D)	A+++
SCOP 35 °C (EN 14825)	4.89
SCOP 55 °C (EN 14825)	4.01
Heating output at A7/W35 (EN 14511)	5.79 kW
Heating output at A2/W35 (EN 14511)	4.82 kW
Heating output at A-7/W35 (EN 14511)	13.15 kW
Max. cooling capacity at A35/W7	10.09 kW
Cooling capacity at A35/W18, partial load (EN 14511)	5.81 kW
Max. cooling capacity at A35/W18	12.95 kW
COP at A7/W35 (EN 14511)	5.41
COP at A2/W35 (EN 14511)	4.41
COP at A-7/W35 (EN 14511)	3.11
Energy efficiency ratio at A35/W7 max.	3.14
Energy efficiency ratio at A35/W18, partial load (EN 14511)	5.41
Energy efficiency ratio at A35/W18 max.	4.11
Sound power level (EN 12102)	45 dB(A)
Min./max. application limits for heat source	-25 / 40 °C
Max. application limit on the heating side	75 °C
Height	1365 mm

Width	1170 mm
Depth	727 mm
Weight	205 kg
Rated voltage, compressor	400 V
Refrigerant	R290
Colour	Signal white RAL 9003

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.