

AWG 560 H-SR

PRODUCT-NO.: 233837

Thermally insulated external wall outlet for air routing from air source heat pumps installed indoors, with oval connection.

The main features

Condensate run marks on the face panel are prevented by a wide drip edge on the frame

Integral rodent guard prevents small animals and leaves getting in

Good protection from weather and low pressure losses, thanks to optimised fin geometry





Type	AWG 560 H-GL	AWG 560 H-SR	AWG 560 L
Part no.	232956	233837	231041
Technical data			
Height	490 mm	490 mm	477 mm
Width	897 mm	897 mm	878 mm
Depth	627 mm	627 mm	625 mm
Nominal diameter	560 mm	560 mm	560 mm
Min. outlet aperture	830x430 mm	830x430 mm	830x430 mm
Wall thickness	280 - 500 mm	280 - 500 mm	280 - 500 mm
Max. air flow rate	3500 m ³ /h	3500 m ³ /h	3500 m ³ /h
Colour	RAL 9006	silver-metallic	Aluminium, anodised
Material	Sheet steel	Sheet steel	Sheet steel
Version	Horizontal with grey painted weather grille	Horizontal weather grille painted in metallic silver	For light well version

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.