

# AWG 560 L

## ACCESSORIES

PRODUCT-NO.: 231041

Thermally insulated external wall outlet for air routing from air source heat pumps installed indoors, with oval connection.

### The main features

Condensate run marks on the wall face are prevented by a wide drip edge on the frame

---

Integral rodent guard prevents small animals and leaves getting in

---

Good protection from weather and low pressure losses, thanks to optimised fin geometry





|          |           |
|----------|-----------|
| Type     | AWG 560 L |
| Part no. | 231041    |

#### Technical data

|                      |                           |
|----------------------|---------------------------|
| Height               | 477 mm                    |
| Width                | 878 mm                    |
| Depth                | 625 mm                    |
| Nominal diameter     | 560 mm                    |
| Min. outlet aperture | 830x430 mm                |
| Wall thickness       | 280 - 500 mm              |
| Max. air flow rate   | 3500 m <sup>3</sup> /h    |
| Colour               | Aluminium,<br>anodised    |
| Material             | Sheet steel               |
| Version              | For light<br>well version |

## **Contact information**

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **[info@stiebel-eltron.co.za](mailto:info@stiebel-eltron.co.za)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.