

UP 50/1-12 E


ACCESSORIES



PRODUCT-NO.: 227423

The main features

When using an IF module, UP 40/1-8 E and UP 50/1-12 E can be controlled via 0-10 V switching

Circulation pump with energy efficiency category A





Type	UP 40/1-8 E	UP 50/1-12 E	UP 25/1-8 PCV
Part no.	227422	227423	235950

Technical data

Energy Efficiency Index EEI	0,23	0,23	0,23
Power consumption	12-310 W	25-590 W	8-130 W
Rated voltage	230 V	230 V	230 V
Fitted length (gauge)	220 mm	220 mm	180 mm
Connection	DN 40	DN 50	G 1 1/2
Head	8,00 m	11,00 m	8,00 m
Max. throughput	15,00 m ³ /h	29,00 m ³ /h	8,00 m ³ /h
Controlled via differential pressure	x	x	x
Control via PWM signal	-	-	x
Controlled via 0-10 V signal with IF module	x	x	-



Type	UP 30/1-8 PCV
------	---------------

Part no.	235951
----------	--------

Technical data

Energy Efficiency Index EEI	0,23
-----------------------------	------

Power consumption	8-130 W
-------------------	---------

Rated voltage	230 V
---------------	-------

Fitted length (gauge)	180 mm
-----------------------	--------

Connection	G 2
------------	-----

Head	8,00 m
------	--------

Max. throughput	8,00 m ³ /h
-----------------	------------------------

Controlled via differential pressure	x
--------------------------------------	---

Control via PWM signal	x
------------------------	---

Controlled via 0-10 V signal with IF module	-
---	---

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.