

# SD DN32-1 E

PRODUCT-NO.: 074414

Pressure hoses for flow and return lines (with 30 mm thermal insulation), operating pressure 0.25 MPa with threaded fittings. With one right angle and one straight end piece.





Type	SD 25-1 E	SD 32-1 E	SD 50-1 E
Part no.	232965	232968	232972

**Technical data**

Connection, heating and source side	G 1 1/4	G 1 1/4	G 2
For pressure hose size DN	25	32	50
Length	1 m	1 m	1 m
Thermal insulation thickness	30 mm	30 mm	50 mm
External diameter incl. insulation	99 mm	106 mm	134 mm
Max. operating pressure	2.50 bar	2.50 bar	2.50 bar



Type	SD DN25-1 E	SD DN32-1 E
Part no.	074415	074414

## Technical data

Connection, heating and source side	G 1 1/4	G 1 1/4
For pressure hose size DN	25	32
Length	1 m	1 m
Thermal insulation thickness	19 mm	19 mm
External diameter incl. insulation	80 mm	86 mm
Max. operating pressure	2.50 bar	2.50 bar

## **Contact information**

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **[info@stiebel-eltron.co.za](mailto:info@stiebel-eltron.co.za)**

## **Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.