


WPL 23 E









AIR | WATER HEAT PUMPS












PRODUCT-NO.: 227758












Obligatory supplies

Article	Part no.	Type	Description
	236000	<u>WPM international</u>	Heat pump manager with international operating instructions, Height: 72 mm, Width: 146 mm, Depth: 96 mm

Additional supplies

Article	Part no.	Type	Description
	074412	<u>ZVK-WPL 13/18/23 I</u>	Casing, Colour: white
	074413	<u>ZVK-WPL 13/18/23 A</u>	Casing, Colour: white
	201620	<u>UP 25/7.5 PCV</u>	Circulation pump, Connection: G 1 1/2
	234763	<u>WPKI 5</u>	Compact installation
	234764	<u>BBI 5</u>	Compact installation
	234348	<u>SBBE 301 WP</u>	DHW cylinder, Rated capacity: 299 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234349	<u>SBBE 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Depth: 852 mm, Height: 1737 mm, Width: 786 mm
	234350	<u>SBBE 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Depth: 852 mm, Height: 1972 mm, Width: 786 mm

	234351	<u>SBBE 501 WP SOL</u>	DHW cylinder, Rated capacity: 495 l, Height: 1972 mm, Width: 786 mm, Depth: 852 mm
	235874	<u>WPIC 3</u>	Air handling module, Height: 637 mm, Width: 1240 mm, Depth: 800 mm
	235199	<u>SBPE 400</u>	Buffer cylinder, Rated capacity: 396 l, Width: 787 mm, Height: 1717 mm, Depth: 852 mm
	235906	<u>SBB 600 WP SOL</u>	DHW cylinder, Rated capacity: 575 l, Height: 1775 mm, Diameter incl. thermal insulation: 970 mm
	235907	<u>SBB 800 WP SOL</u>	DHW cylinder, Rated capacity: 770 l, Height: 1943 mm, Diameter incl. thermal insulation: 1010 mm
	235908	<u>SBB 1000 WP SOL</u>	DHW cylinder, Rated capacity: 835 l, Height: 2153 mm, Diameter incl. thermal insulation: 1010 mm
	235950	<u>UP 25/1-8 PCV</u>	Circulation pump
	233602	<u>WPKI-HK E</u>	Heating circuit assembly without mixing valve
	233603	<u>WPKI-HKM E</u>	Heating circuit assembly with mixing valve
	231890	<u>ZVK-WPL 13/18/23 A SR</u>	Casing, Colour: silver
	232956	<u>AWG 560 H-GL</u>	Grey painted wall transition with weather grille, thermally insulated
	232957	<u>AWG 560 V-GL</u>	Grey painted wall transition with weather grille, thermally insulated
	233837	<u>AWG 560 H-SR</u>	Wall outlet with weather grille, thermally insulated
	233838	<u>AWG 560 V-SR</u>	Wall outlet with weather grille, thermally insulated

	231041	<u>AWG 560 L</u>	Wall outlet for light shaft, thermally insulated
	231044	<u>AWG 600 L</u>	Wall outlet with weather grille, thermally insulated
	003478	<u>Hose connection plate DN 560</u>	Hose connection panel
	185325	KSD 1	Duct silencer, Colour: white
	229286	<u>PK 10</u>	Condensate pump with hose connection, Max. head: 5 m, Max. pump rate: 500 l/h
	185579	<u>FE 7</u>	Remote control with room sensor, Height: 80,00 mm, Width: 80,00 mm, Depth: 30 mm
	074415	<u>SD 25-1</u>	Pressure hose, angled, with 19 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 80 mm, Connections for the heating and source side: G 1 1/4
	232974	<u>SD 25-1 KE</u>	Pressure hose (can be trimmed), angled, DN 25, 1 m with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 1 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	233828	<u>SD 25-2 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	232971	<u>SD 25-2.5 GE</u>	Pressure hose, straight, with 30 mm thermal insulation, For pressure hose size DN: 25, Length: 2,5 m, External diameter with insulation: 99 mm, Connections for the heating and source side: G 1 1/4
	233711	STB-FB	Safety thermostat, underfloor heating system

	070634	<u>WT 20</u>	Heat exchanger, Height: 313 mm, Width: 113 mm, Depth: 136.5 mm
	221360	<u>SBB 301 WP</u>	DHW cylinder, Rated capacity: 301 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221361	<u>SBB 302 WP</u>	DHW cylinder, Rated capacity: 290 l, Diameter incl. thermal insulation: 700 mm, Height: 1710 mm
	221362	<u>SBB 401 WP SOL</u>	DHW cylinder, Rated capacity: 395 l, Height: 1880 mm, Diameter incl. thermal insulation: 750 mm
	185458	<u>SBP 200 E</u>	Buffer cylinder, Rated capacity: 207 l, Height: 1535 mm, Diameter incl. thermal insulation: 630 mm
	220824	<u>SBP 400 E</u>	Buffer cylinder, Rated capacity: 415 l, Height: 1710 mm, Diameter incl. thermal insulation: 750 mm
	227564	<u>SBP 1000 E</u>	Buffer cylinder, Rated capacity: 1006 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	227566	<u>SBP 1000 E SOL</u>	Buffer cylinder, Rated capacity: 979 l, Height: 2300 mm, Diameter incl. thermal insulation: 1010 mm
	229980	<u>SBS 601 W</u>	Instantaneous water cylinder, Rated capacity: 613 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229984	<u>SBS 601 W SOL</u>	Instantaneous water cylinder, Rated capacity: 599 l, Height: 1665 mm, Diameter incl. thermal insulation: 970 mm
	229981	<u>SBS 801 W</u>	Instantaneous water cylinder, Rated capacity: 759 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm
	229985	<u>SBS 801 W SOL</u>	Instantaneous water cylinder, Rated capacity: 740 l, Height: 1830 mm, Diameter incl. thermal insulation: 1010 mm



229982

SBS 1001 W

Instantaneous water cylinder, Rated capacity:
941 l, Height: 2240 mm, Diameter incl. thermal
insulation: 1010 mm



229986

SBS 1001 W SOL

Instantaneous water cylinder, Rated capacity:
916 l, Height: 2240 mm, Diameter incl. thermal
insulation: 1010 mm

Contact information

You have questions? We appreciate to help you:
Call +27 10 001 85 47 Write an email to info@stiebel-eltron.co.za

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.