

# WDH 1000 SBP

ACCESSORIES

PRODUCT-NO.: 231929

High grade EPTS rigid foam thermal insulation with insulation cover and floor disc for SBP 1000-1500 buffer cylinders. Graphite inserts in the EPTS and fleece for lowest heat losses. Wedge-shaped cut-outs and fleece layer ensure an optimum match to the cylinder. Prepared adhesive joint in the wedge-shaped cut-outs enables adjustment to the shape prior to installation. External plastic jacket in white; cover in basalt grey. Thermal insulation secured with a quick-release hook strip.



## The main features

Suitability for cooling operation WDH...cool only in conjunction with cylinder SBP...E cool being pre-insulated

---

Prepared to be shaped into a semi-shell insulation

---

Graphite inclusions for best insulation properties

---

Composite thermal insulation made from rigid foam and fleece



Type	WDH 1000 SBP	WDH 1500 SBP
Part no.	231929	231930
Standby energy consumption/24 h at 65 °C	3,6 kWh	4,1 kWh
Insulation for	SBP 1000 E and E SOL	SBP 1500 E and E SOL
Height	2340 mm	2255 mm
Thickness	110 mm	110 mm

#### Technical data

---

**Contact information**

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **[info@stiebel-eltron.co.za](mailto:info@stiebel-eltron.co.za)**

**Installation information**

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.