








SBB 302 WP

DHW CYLINDER

PRODUCT-NO.: 221361

Additional supplies

Article	Part no.	Type	Description
	232030	<u>BGC 2/60</u>	Threaded immersion heater, Depth of insertion: 480 mm
	233719	<u>UPZ</u>	DHW circulation pump, Connection: G 1/2
	075115	<u>BGC/45</u>	Threaded immersion heater, Depth of insertion: 455 mm
	071330	<u>FCR 21/60</u>	Flanged immersion heater, Connected load with ~ 230 V: 2-4 kW, Connected load with ~ 400 V: 2-6 kW, Version: Single/two line
	071331	<u>FCR 21/120</u>	Flanged immersion heater, Connected load with ~ 230 V: 4 kW, Connected load with ~ 400 V: 8/12 kW, Version: Single circuit
	074370	<u>ZH 1</u>	Safety assembly ZH 1 for sealed unvented electric floorstanding cylinders pressure reducing valve DMV/ZH1, may be retrofitted. Brass casing, G 3/4 connections. Response pressure, safety relief valve: 0,6 MPa, Connection: G 3/4 A
	074371	DMV / ZH 1	Special pressure reducing valve G 1 as supplement to ZH 1, if the static pressure at the installation location exceeds 0.48 MPa (4.8 bar). Brass. Connection 3/4 inch.

Contact information

You have questions? We appreciate to help you:
Call +27 10 001 85 47 Write an email to info@stiebel-eltron.co.za

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.