


SBP 1500 E SOL






HEATING BUFFER CYLINDER








PRODUCT-NO.: 227567

Obligatory supplies

Article	Part no.	Type	Description
	231930	<u>WDH 1500 SBP</u>	Thermal insulation, Standby energy consumption/24 h at 65 °C: 4,1 kWh, Insulation for: SBP 1500 E and E SOL, Thickness: 110 mm, Height: 2255 mm

Additional supplies

Article	Part no.	Type	Description
	231930	<u>WDH 1500 SBP</u>	Thermal insulation, Standby energy consumption/24 h at 65 °C: 4,1 kWh, Insulation for: SBP 1500 E and E SOL, Thickness: 110 mm, Height: 2255 mm
	234503	<u>FCR 28/120 CrNi</u>	Flanged immersion heater, Connected load with ~ 400 V: 6/12 kW, Version: Single/two line
	231884	<u>BF 80</u>	Blank flange, Flange diameter: DN 80
	231885	<u>FG 80/2</u>	Flanged reducer DN 80 / G 2 A, Flange diameter: DN 80, Threaded connection: G 2 A
	232030	<u>BGC 2/60</u>	Threaded immersion heater, Depth of insertion: 480 mm
	075124	<u>FCR 28/360 Si</u>	Flanged immersion heater, Connected load with ~ 400 V: 36 kW, Version: Single circuit
	075131	<u>FCR 28/180 Si</u>	Flanged immersion heater, Connected load with ~ 400 V: 18 kW, Version: Single circuit

	075140	FCR 28/120 Si	Flanged immersion heater, Connected load with ~ 400 V: 12 kW, Version: Single circuit
	075141	FCR 28/270 Si	Flanged immersion heater, Connected load with ~ 400 V: 27 kW, Version: Single circuit
	000694	<u>FCR 28/120</u>	Flanged immersion heater, Connected load with ~ 400 V: 12 kW, Version: Single circuit
	000695	<u>FCR 28/180</u>	Flanged immersion heater, Connected load with ~ 400 V: 18 kW, Version: Single circuit
	000696	<u>FCR 28/270</u>	Flanged immersion heater, Connected load with ~ 400 V: 27 kW, Version: Single circuit
	001502	<u>FCR 28/360</u>	Flanged immersion heater, Connected load with ~ 400 V: 36 kW, Version: Single circuit
	071332	<u>FCR 28/120</u>	Flanged immersion heater, Connected load with ~ 400 V: 6/12 kW, Version: Single/two line
	071333	<u>FCR 28/180</u>	Flanged immersion heater, Connected load with ~ 400 V: 9/18 kW, Version: Single/two line

Contact information

You have questions? We appreciate to help you:
Call +27 10 001 85 47 Write an email to info@stiebel-eltron.co.za

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.