Accessories

FCR 21/120 E

ORDER NO: 071331



FCR 28/120

ORDER NO: 071332

Key features

- Replaceable copper heating element
- For matching to individual usage scenarios
- High hot water convenience thanks to powerful heating elements
- Variable temperature setting via rotary selector

STIEBEL ELTRON

Technical data sheet





Type	FCR 21/120 E ORDER NO: 071331	FCR 28/120 ORDER NO: 071332
Order No	071331	071332
Electrical data		
Connected load ~ 230 V	4 kW	
Connected load ~ 380 V	7.2/10.8 kW	
Connected load ~ 400 V	8/12 kW	6/12 kW
Power supply	1/N/PE, 2/N/PE, 3/PE	3/PE
Single circuit operating mode	X	X
Rated voltage	230/400 V	400 V
Coil voltage	230 V	230 V
Frequency	50/60 Hz	50 Hz
Application limits		
Temperature setting range	35-82 °C	35-85 °C
Max. permissible pressure	1.00 MPa	1.00 MPa
Minimum cylinder diameter	450 mm	550 mm
Minimum cylinder volume	200 l	300 l
Versions		
Version	Single circuit	Dual/single circuit

Integral contactor	-	X
IP rating	IP24	IP24

Dimensions

Immersion depth	400 mm	450 mm
Flange external diameter	210 mm	280 mm
Torque	55 nm	80 nm

Weights

Weight	12.00 kg	12.00 kg

Values

Flange diameter	210 mm	280 mm

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za