Accessories

BGC/45

ORDER NO: 075115



Key features

- Threaded immersion heater for sealed unvented heating systems and DHW heating systems.
- For matching to individual usage scenarios
- High hot water convenience thanks to powerful heating elements
- Variable temperature setting via rotary selector

STIEBEL ELTRON

Technical data sheet



Type	BGC/45 ORDER NO: 075115
Order No	075115

Electrical data

Connected load ~ 230 V	2-4 kW
Connected load ~ 400 V	6 kW
Power supply	1/N/PE, 2/PE, 3/PE
Single circuit operating mode	X
Rated voltage	230/400 V
Frequency	50/60 Hz

Application limits

Temperature setting range	10-80 °C
Max. permissible pressure	1.00 MPa
Minimum cylinder diameter	450 mm
Minimum cylinder volume	50 l

Versions

Version	Universal flange
For use in	DHW cylinder/ Buffer cylinder/ Instantaneous water cylinder

Installation position	Horizontal
IP rating	IP44

Dimensions

Immersion depth	455 mm

Weights

Weight	2.50 kg

Values

Volume range of the cylinder	200.00–1,500.00 l
Volume above the heating element (max.)	600.00 l

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za