Accessories

UP 25/7.5 PCV

ORDER NO: 201620



UP 25/1-8 PCV

ORDER NO: 205285

UP 30/1-8 PCV

ORDER NO: 205286

Key features

- Electronically controlled circulation pump with variable differential control
- Energy efficiency index (EEI): 0.20
- Can be controlled via either a PWM signal or differential pressure
- Delivery head max. 10 m

STIEBEL ELTRON

Technical data sheet





Type	UP 25/1-8 PCV ORDER NO: 205285	UP 25/7.5 PCV ORDER NO: 201620	UP 30/1-8 PCV ORDER NO: 205286
Order No	205285	201620	205286
Energy data			
Energy Efficiency Index EEI	0.20	0.20	0.20
Connections			
Connection	G 1 1/2	G 1 1/2	G 2
Values			
Delivery head	8.00 m	8.40 m	8.00 m
Max. flow rate	9.50 m³/h	4.00 m³/h	9.00 m³/h
Application limit	-20 - 110 °C		-20 - 110 °C
Max. operating temperature	70 °C		70 °C
Max. operating pressure	1 MPa	10 MPa	1 MPa
Electrical data			
Power consumption	200 W	10-60 W	130 W
Electrical connection	1/N~230 V	1/N/PE~230 V	1/N~230 V
Rated voltage	230 V	230 V	230 V

Versions

Control via 0-10 V signal with IF module	x	-	x
Control via differential pressure	x	x	x
Control via PWM signal	x	x	x
IP rating	IPX4	IPX4	IPX4

Dimensions

Installation length (centre distance)	180 mm	180 mm	180 mm

Weights

Weight	3.7 kg		3.2 kg

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za