Heating buffer cylinder

SBP 200 Plus cool

ORDER NO: 205295



Key features

- Connector for an electric threaded immersion heater in both the upper and lower third
- Suitable for both heating and cooling modes
- Prepared for self-consumption of electricity from photovoltaic systems
- New appealing design

STIEBEL ELTRON

Technical data sheet



Type	SBP 200 Plus cool ORDER NO: 205295
Order No	205295

Energy data

Standby losses S	51.5 W
Standby energy consumption/24 h at 65 °C	1.235 kWh

Hydraulic data

Cylinder volume V	207 l
Nominal capacity	207 l

Application limits

Max. permissible pressure	0.30 MPa
Test pressure	0.45 MPa
Max. charge/discharge flow rate	1.60 m³/h
Max. permissible temperature	95 °C

Dimensions

Height	1510 mm
Diameter	600 mm
Height when tilted	1637 mm

Weights

Weight, full	265 kg
Weight, empty	58 kg

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za