Convectors

CNS 150 Trend M (ZA)

ORDER NO: 205903



CNS 50 Trend M (ZA)

ORDER NO: 204503

CNS 100 Trend M (ZA)

ORDER NO: 204504

Key features

- Wall mounted convector heaters with high heating output
- Compact metal casing in a slimline design
- Mechanical temperature controller
- Omnipolar operating selector
- Safety through overheating protection
- Long lasting stainless steel tubular heater with steel fins

STIEBEL ELTRON

Technical data sheet





Type	CNS 50 Trend M (ZA) ORDER NO: 204503	CNS 100 Trend M (ZA) ORDER NO: 204504	CNS 150 Trend M (ZA) ORDER NO: 205903
Order No	204503	204504	205903
Electrical data			
Power supply	1/N/PE	1/N/PE	1/N/PE ~ 230 V
Rated voltage	230 V	230 V	230 V
Voltage range	230 V	230 V	
Frequency	50/- Hz	50/- Hz	50/- Hz
Rated current	2,2 A	4,3 A	6,5 A
Connected load	0,5 kW	1 kW	1,5 kW
Phases	1/N/PE	1/N/PE	1/N/PE
Fuse protection	10 A	10 A	10 A
Versions			
Number of heating stages	1	1	1
IP rating	IP24	IP24	IP24
Protection class	I	I	I
Colour	alpine white	alpine white	alpine white
Frost protection setting	7 °C	7 °C	7 °C
Safety system	High limit safety cut-out with automatic reset	High limit safety cut-out with automatic reset	High limit safety cut-out with automatic reset

Version	Wall mounted appliance	Wall mounted appliance	Wall mounted appliance
Values			
Setting range	5-35 °C	5-35 °C	5-35 °C
Dimensions			
Height	450 mm	450 mm	450 mm
Width	348 mm	426 mm	582 mm
Depth	100 mm	100 mm	100 mm
Weights			
Weight	4.00 kg	4.60 kg	6.00 kg
Energy data			
Rated heating output Pnom	0.50 kW	1.00 kW	1.50 kW
Maximum continuous heating output Pmax,c	0.50 kW	1.00 kW	1.50 kW
Minimum heating output (standard value) Pmin	0.00 kW	0.00 kW	0.00 kW
Room heating seasonal efficiency ηs	31 %	31 %	31 %
with minimum heating output elmin	0.00 kW	0.00 kW	0.00 kW
with rated heating output elmax	0.00 kW	0.00 kW	0.00 kW
in standby mode elSB	0.00 kW	0.00 kW	0.00 kW
Room temperature control with window open detection	-	-	-
Room temperature control with presence detection	-	-	-

Single stage heating output, no room temperature control	–	–	–
Electronic room temperature control plus day timer	–	–	–
Electronic room temperature control plus week timer	–	–	–
With electronic room temperature control	–	–	–
Room temperature control with mechanical thermostat	x	x	x
Two or more manual stages, no room temperature control	–	–	–
With adaptive start control	–	–	–
With working time limitation	–	–	–
With distance control option	–	–	–
With black bulb sensor	–	–	–

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za