Air source heat pumps

WPL-A 10.2 Plus HK 400

ORDER NO: 206125



WPL-A 07.2 Plus HK 230

ORDER NO: 206122

WPL-A 10.2 Plus HK 230

ORDER NO: 206124

WPL-A 13.2 Plus HK 400

ORDER NO: 206127

Key features

- Air source heat pump installed outdoors for modernisation and new build
- Also suitable for densely built-up areas due to very low operating noise
- Compact mono block version in a timeless design
- Efficient cooling possible thanks to circuit reversal
- Many solutions for different applications possible with flexible installation options and customised accessories
- Multi stage safety concept for the R290 refrigerant circuit






Type	WPL-A 07.2 Plus HK 230 ORDER NO: 206122	WPL-A 10.2 Plus HK 230 ORDER NO: 206124	WPL-A 10.2 Plus HK 400 ORDER NO: 206125	WPL-A 13.2 Plus HK 400 ORDER NO: 206127
Order No	206122	206124	206125	206127
Energy data				
Energy efficiency class, heat pump W35 (A+++ – D)	A+++	A+++	A+++	A+++
Energy efficiency class, heat pump W55 (A+++ – D)	A+++	A+++	A+++	A+++
SCOP 35 °C (EN 14825)	5.09	4.96	4.96	4.89
SCOP 55 °C (EN 14825)	4.02	3.99	3.99	4.01
	6.49	6.11	6.11	6.97
	4.72	4.70	4.70	5.05
Heating output				
Heating output at A7/W35 (min./max.)	2,76 / 8,47 kW	3,69 / 11,97 kW	3,69 / 11,97 kW	5,11 / 15,31 kW
Heating output at A2/W35 (min./max.)	2,36 / 6,96 kW	3,05 / 9,84 kW	3,05 / 9,84 kW	4,36 / 13,04 kW
Heating output at A-7/W35 (min./max.)	1,71 / 7,09 kW	2,67 / 10,07 kW	2,67 / 10,07 kW	3,21 / 13,15 kW
Heating output at A7/W35 (EN 14511)	3.05 kW	4.32 kW	4.32 kW	5.79 kW
Heating output at A7/W55 (EN 14511)	2.65 kW	4.05 kW	4.05 kW	5.10 kW
Heating output at A2/W35 (EN 14511)	3.29 kW	4.09 kW	4.09 kW	4.82 kW
Heating output at A2/W35 (EN 14511) with defrosting	4.30 kW	5.92 kW	5.92 kW	8.10 kW
Heating output at A2/W55 (EN 14511)	4.43 kW	6.14 kW	6.14 kW	8.14 kW
Heating output at A-7/W35 (EN 14511)	7.09 kW	10.07 kW	10.07 kW	13.15 kW
Heating output at A-7/W55 (EN 14511)	7.09 kW	10.02 kW	10.02 kW	13.11 kW

Heating output at A-7/W65 (EN 14511)	6.71 kW	9.65 kW	9.65 kW	12.89 kW
Heating output at A-7/W75 (EN 14511)	5.64 kW	8.33 kW	9.00 kW	12.32 kW
Cooling capacity at A35/W7, partial load (EN 14511)	2.32 kW	3.53 kW	3.53 kW	4.29 kW
Max. cooling capacity at A35/W7	6.51 kW	9.33 kW	9.33 kW	10.09 kW
Cooling capacity at A35/W18, partial load (EN 14511)	3.15 kW	4.29 kW	4.29 kW	5.81 kW
Max. cooling capacity at A35/W18	6.98 kW	10.51 kW	10.51 kW	12.95 kW

Power consumption

Power consumption at A7/W35 (EN 14511)	0.56 kW	0.80 kW	0.80 kW	1.07 kW
Power consumption at A7/W55 (EN 14511)	0.83 kW	1.27 kW	1.27 kW	1.56 kW
Power consumption at A2/W35 (EN 14511)	0.72 kW	0.90 kW	0.90 kW	1.09 kW
Power consumption at A2/W35 (EN 14511) with defrosting	1.01 kW	1.41 kW	1.41 kW	1.97 kW
Power consumption at A2/W55 (EN 14511)	1.56 kW	2.12 kW	2.12 kW	2.82 kW
Power consumption at A-7/W35 (EN 14511)	2.18 kW	3.20 kW	3.20 kW	4.23 kW
Power consumption at A-7/W55 (EN 14511)	2,74 kW	4,04 kW	4,04 kW	5,24 kW
Power consumption at A-7/W65 (EN 14511)	3.37 kW	4.79 kW	4.79 kW	6.41 kW
Power consumption at A-7/W75 (EN 14511)	3.57 kW	5.44 kW	5.88 kW	7.63 kW

Coefficients of performance

COP at A7/W35 (EN 14511)	5.50	5.40	5.40	5.41
COP at A7/W55 (EN 14511)	3.19	3.18	3.18	3.26
COP at A2/W35 (EN 14511)	4.57	4.54	4.54	4.41
COP at A2/W35 (EN 14511) with defrosting	4.26	4.21	4.21	4.10
COP at A2/W55 (EN 14511)	2.84	2.90	2.90	2.89
COP at A-7/W35 (EN 14511)	3.25	3.15	3.15	3.11

COP at A-7/W55 (EN 14511)	2.58	2.48	2.48	2.50
COP at A-7/W65 (EN 14511)	1.99	2.02	2.02	2.01
COP at A-7/W75 (EN 14511)	1.58	1.53	1.53	1.62
Energy efficiency ratio at A35/W7, partial load (EN 14511)	3.83	3.87	3.87	3.95
Energy efficiency ratio at A35/W7 max.	2.97	2.76	2.76	3.14
Energy efficiency ratio at A35/W18, partial load (EN 14511)	5.29	5.46	5.46	5.41
Energy efficiency ratio at A35/W18 max.	4.28	4.01	4.01	4.11

Sound emissions

Sound power level (EN 12102)	43 dB(A)	46 dB(A)	46 dB(A)	45 dB(A)
Max. sound power level	57 dB(A)	59 dB(A)	59 dB(A)	60 dB(A)
Sound power level, max. reduced night mode	47 dB(A)	49 dB(A)	49 dB(A)	50 dB(A)

Application limits

Min. application limit, heat source	-25 °C	-25 °C	-25 °C	-25 °C
Max. application limit, heat source	40 °C	40 °C	40 °C	40 °C
Min. application limit on heating side	15 °C	15 °C	15 °C	15 °C
Max. application limit on the heating side	75 °C	75 °C	75 °C	75 °C
Min. cooling mode application limit for outside temperature	15 °C	15 °C	15 °C	15 °C
Max. cooling mode application limit for outside temperature	45 °C	45 °C	45 °C	45 °C
Min./max. application limit, heating, outside temperature	-25 / 40 °C	-25 / 40 °C	-25 / 40 °C	-25 / 40 °C
Min./max. application limit, heating, flow temperature	15 / 75 °C	15 / 75 °C	15 / 75 °C	15 / 75 °C
Min./max. application limit, cooling, outside temperature	15 / 45 °C	15 / 45 °C	15 / 45 °C	15 / 45 °C
Operating pressure	0.25 MPa		0.25 MPa	0.25 MPa

Dimensions

Height	960 mm	1144 mm	1144 mm	1365 mm
Width	1170 mm	1170 mm	1170 mm	1170 mm
Depth	727 mm	727 mm	727 mm	727 mm

Weights

Weight	142 kg	166 kg	166 kg	203 kg

Electrical data

Rated voltage, compressor	230 V	230 V	400 V	400 V
Rated voltage, control unit	230 V	230 V	230 V	230 V
Phases, compressor	1/N/PE	1/N/PE	3/N/PE	3/N/PE
Phases, control unit	1/N/PE	1/N/PE	1/N/PE	1/N/PE
Compressor fuse protection	1 x B 16 A	1 x B 25 A	3 x B 10 A	3 x B 16 A
Control unit fuse protection	1 x B 16 A	1 x B 16 A	1 x B 16 A	1 x B 16 A
Max. power consumption, heat pump	3.7 kW	5.8 kW	6.8 kW	8.3 kW
Starting current	8.4 A		5.2 A	4.8 A
Max. operating current	15.50 A	24.90 A	9.70 A	13.00 A
Power factor cos(phi)	0.95		0.95	0.95
Frequency	50 Hz	50 Hz	50 Hz	50 Hz

Hydraulic data

Design flow rate A-7/W35 7K	0.92 m³/h	1.31 m³/h	1.31 m³/h	1.74 m³/h

Internal pressure drop at design volume rate	102 hPa	137 hPa	137 hPa	207 hPa
kVS value	2.87 m³/h	3.53 m³/h	3.53 m³/h	3.83 m³/h
Min. flow rate, heating	0.30 m³/h	0.42 m³/h	0.42 m³/h	0.54 m³/h
Min. flow rate, defrosting	0.53 m³/h	0.72 m³/h	0.72 m³/h	0.90 m³/h
Standard flow rate to EN 14511, low temperature application	0.5 m³/h	0.8 m³/h	0.8 m³/h	1.0 m³/h
Standard flow rate to EN 14511, average temperature application	0.3 m³/h	0.4 m³/h	0.4 m³/h	0.6 m³/h
Min. flow rate, heating	0.30 m³/h	0.42 m³/h	0.42 m³/h	0.54 m³/h

Values

Flow rate on heat source side	2990 m³/h		4600 m³/h	5780 m³/h

Versions

Refrigerant	R290	R290	R290	R290
Refrigerant charge	1,4 kg	1,6 kg	1,6 kg	2,15 kg
Global warming potential of the refrigerant (GWP100)	3	3	3	3
CO2 equivalent (CO2e)	0.0042 t	0.0048 t	0.0048 t	0.00645 t
IP rating	IP14B	IP14B	IP14B	IP14B
Defrost type	Circuit reversal	Circuit reversal	Circuit reversal	Circuit reversal
Frost protection	•	•	•	•
Colour	Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021	Dark grey RAL 7021
Condenser material	1.4401/Cu	1.4401/Cu	1.4401/Cu	1.4401/Cu

Connections

Connection, heating flow/return	G 1 1/4 A	G 1 1/4 A	G 1 1/4 A	G 1 1/4 A

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za