Small water heater

SHC 10 AU

ORDER NO: 235002



Key features

- Supplies multiple draw-off points via a pressurised connection
- Enamelled pressure-tested steel inner cylinder
- Frost protection setting
- Quick and easy installation

STIEBEL ELTRON

Technical data sheet



Type	SHC 10 AU ORDER NO: 235002
Order No	235002

Electrical data

Rated output 2	1,5 kW
Fuse protection 2	10 A
Frequency	50-60 Hz

Hydraulic data

Nominal capacity	10 l
Mixed water amount at 40 °C	15,3 l

Application limits

Temperature setting range	30-65 °C
Max. water inlet pressure	0.70 MPa
Max. permissible pressure	0.70 MPa
Min. water inlet pressure	0.10 MPa

Versions

Type	pressurised
Installation type	Undersink

With tap	-
Inner cylinder material	Steel, enamelled
Cylinder material	Steel
With thermal insulation	•
Casing material	Plastic
Colour	white
Cable length	1 m
Operation	manual
Temperature limit	•
IP rating	IP24 D

Connections

Water connection	G 1/2 A

Dimensions

Height	498 mm
Width	280 mm
Depth	270 mm

Weights

Weight	7.20 kg

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za