Instantaneous water heater for showers

DX 45 E (EX)

ORDER NO: 236257



Key features

- Temperature adjustment via stepless power control using rotary knob
- Highly efficient composite polymer tank for reduced heat loss and electricity saving
- Complete set optimised for a single shower
- 5-in-1 shower head with wall bracket
- Anti-scalding and overheating protection with double action thermostat
- Protection from electric shock with Earth Leakage Sensing Device (ELSD)
- Protection class IP25 (splash-proof)
- Quick and easy installation

STIEBEL ELTRON

Technical data sheet



Type	DX 45 E (EX) ORDER NO: 236257
Order No	236257

Connections

Cold water connection	1/2 inch

Electrical data

Electrical fuse protection	ELSD
Rated output	4,500 W
Rated current	20.5 A
Display	without

Versions

Heating element	Copper tubular
Type	Open outlet
Automatic flow switch	true
Heating material	Plastic
Temperature setting	Variable
Temperature control	Output control
Anti-scalding protection	Double acting thermostat

Shower accessories	5-in-1 shower head with wall mounting bracket
Colour	white
IP rating	IP25
Installation site	Wall

Application limits

Shutdown value	0.8 l/min
Starting flow rate	1.3 l/min
Max. water inlet pressure	0.5 MPa
Min. water inlet pressure	0.015 MPa

Dimensions

Depth	76 mm
Height	264 mm
Width	186 mm

Weights

Weight	0.94 kg

STIEBEL ELTRON

Contact information

You have questions? We appreciate to help you:

Call **+27 10 001 85 47** Write an email to **info@stiebel-eltron.co.za**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.

Website

www.stiebel-eltron.co.za